



### ROOF FRAMING PLAN

Scale: 1/4" = 1'-0"

**ROOF FRAMING NOTES:**

- SEE SHEET S3 FOR TYPICAL DETAILS AND GENERAL NOTES.
- ALL ROOF BEAMS SHALL BE FASTENED TO WALLS OR OTHER SUPPORTS.
- THE DOWN ALL ROOF BEAMS w/ SIMPSON STRB TIES or CDS STRAPS AT ALL BEARING LOCATIONS UNLESS NOTED OTHERWISE.
- FASTEN ALL STEEL BEAMS THROUGH BOTTOM FLANGE USING (2) 1/2" LAG SCREWS INTO WALLS.
- PROVIDE (1) 2x6 TRIM AND (1) 2x6 KING UNLESS NOTED OTHERWISE.
- ALL GABLE END WALLS TO BE BALLOON FRAMED FROM FLOOR TO CEILING.
- SHEATH ROOF w/ 5/8" PLYWOOD C-D GRADE w/ EXTERIOR GLEIT, 1/2" PANEL INDEX, or 1/2" OSB SHEATHING.
- PANEL EDGES OF SHEATHING SHALL BE BUTTED TOGETHER AND CENTERED OVER THE FRAMING MEMBERS HAVING NOMINAL WIDTH OF 2" or GREATER w/ NAILS PLACED NOT LESS THAN 1/2" INCH FROM THE PANEL EDGE.
- ATTIC TRUSS LOADS (SHOW 50 psf, LIVE = 50 psf, DEAD = 20 psf)

**KEY**

- - POST BELOW (1) 2x6 MINIMUM UNLESS NOTED OTHERWISE

NO.	DATE	DESCRIPTION	DRAWN BY	REVIEWED BY
1	8/12/08	C.D. SET	CRD	KAO

PROJECT # D08080

**ASCENT**  
CIVIL & STRUCTURAL ENGINEERING  
1738 Wynkoop Street, Suite 300  
Denver, CO 80202  
303.282.8477 fax 282.8478

ROOF FRAMING PLAN  
**WALLACE RESIDENCE**  
8295 S. KRAMERIA WAY  
CENTENNIAL, COLORADO